AVN-BASED MOS GUIDANCE - THE 0000/1200 UTC ALPHANUMERIC MESSAGES

bv

J. Paul Dallavalle and Mary C. Erickson

1. INTRODUCTION

This Technical Procedures Bulletin (TPB) describes the format and contents of the AVN MOS alphanumeric messages generated during the 0000 and 1200 UTC forecast cycles. These messages contain forecasts of the max/min temperature; time-specific surface temperature and dew point; total sky cover; surface wind direction and wind speed; probability of precipitation (PoP) for 6- and 12-h periods; categories of quantitative precipitation for 6- and 12-h periods; probability of thunderstorms and conditional probability of severe thunderstorms for 6- and 12-h periods; conditional probability of precipitation type (freezing, snow, or liquid) and a corresponding category; snowfall amount; and categories of ceiling height, visibility, and obstruction to vision. Guidance is provided for projections of 6 to 72 hours for most weather elements. Note that a particular element line (see Sections 3 - 20) is not included in the message when all of the forecasts in that line are unavailable. The messages became operational during the 1200 UTC forecast cycle on May 30, 2000. This TPB has been revised to correct the description of the thunderstorm and snowfall amount guidance, and to list the communication headers of messages transmitted to the Air Force Weather Agency (AFWA). When this TPB was revised in August 2001, the snowfall amount guidance was not yet available.

2. MESSAGE HEADING

 KALB
 AVN MOS GUIDANCE
 10/24/2000
 0000 UTC

 DT /OCT 24
 /OCT 25
 /OCT 26
 /

 HR
 06 09 12 15 18 21 00 03 06 09 12 15 18 21 00 03 06 09 12 18 00
 12 18 00

The message heading shown above (see Figs. 1 and 2 also) identifies the station for which the guidance is valid, the forecast cycle, and the day and hour for which the forecasts are valid. In this example, the message is valid for Albany, NY (KALB). All stations are identified by the ICAO four-character identifier.

The "AVN MOS GUIDANCE" appearing on the same line as the station call letters identifies the message contents. The date of the forecast cycle during which the message is issued follows this information. The form of mm/dd/yyyy where mm is the month (1 through 12), dd is the day (1 through 31), and yyyy is the four-digit year is used. The forecast cycle is identified by the standard 0000 or 1200 UTC. In this example, the MOS guidance for KALB was issued from the 0000 UTC forecast cycle of the AVN on October 24, 2000.

The DT and HR lines denote the date and hour at which the forecasts are valid. The DT line indicates the day of the month. Note that the month is denoted by the standard three or four letter abbreviation. For temperature, dew point, sky cover, wind direction and speed, precipitation type, ceiling height, visibility, and obstruction to vision, the date and hour denote the specific time that the forecasts are valid. These forecasts are valid every 3 hours until 60 hours after initial time and then every 6 hours until 72 hours after initial time. For PoP, quantitative precipitation, thunderstorms, severe weather, and snowfall amount, the time indicates the end of the period over which the forecasts are valid. For the max/min temperature, the date group gives only the approximate ending time of the daytime and nighttime periods for which the max and min temperature guidance, respectively, are valid.

3. X/N - MAXIMUM/MINIMUM TEMPERATURE

KALB	2	AVN	MOS	G G	JIDZ	ANCI	Ξ	10,	/24,	/200	00	000) O (JTC							
DT /O	CT	24					/00	ст 2	25						/00	ст 2	26				/
HR	06	09	12	15	18	21	00	03	06	09	12	15	18	21	00	03	06	09	12	18	00
x/n							49				30				61				43		61

The max/min surface temperature forecasts are displayed for projections of 24, 36, 48, 60, and 72 hours after the initial data time (0000 or 1200 UTC). Although the forecasts are presented at consecutive 12-h intervals, each forecast is actually valid for a daytime or nighttime period. For the AVNbased MOS guidance, daytime is defined as 7 a.m. to 7 p.m. Local Standard Time (LST). Nighttime is defined as 7 p.m. to 8 a.m. LST. Thus, the valid date in the appropriate column of the DT and HR lines must be converted by the forecaster to his/her local date. This local date then denotes the appropriate daytime or nighttime for the max or min temperature forecast. For the 0000 UTC forecast cycle, the temperatures are shown in max/min (X/N) order and are valid for today's max, tonight's min, tomorrow's max, tomorrow night's min, and the day after tomorrow's max. For the 1200 UTC cycle, the temperatures are shown in min/max (N/X) order and are valid for tonight's min, tomorrow's max, tomorrow night's min, the day after tomorrow's max, and the night after tomorrow night's min. Each temperature forecast is presented to the nearest whole degree Fahrenheit, and three characters are allowed. A missing forecast is indicated by a 999.

4. TMP - SURFACE TEMPERATURE

F	AL	в	F	NVN	MOS	GU	JIDF	NCE	2	10/	/24/	200	00	000)Ο τ	JTC							
D	т	/00	СТ	24					/00	СТ 2	25						/00	СТ 2	26				/
F	IR		06	09	12	15	18	21	00	03	06	09	12	15	18	21	00	03	06	09	12	18	00
Г	'MP		32	30	30	41	47	47	38	34	32	32	34	47	58	60	54	50	48	47	49	57	53

Time-specific 2-m temperature forecasts are valid every 3 hours from 6 to 60 hours, and then every 6 hours to 72 hours after 0000 and 1200 UTC. These forecasts are valid at 0600, 0900,..., 2100, 0000 UTC, and so forth. Each temperature forecast is presented to the nearest whole degree Fahrenheit; a missing forecast is indicated by a 999. Only three characters are available for the temperature forecasts. Thus, two consecutive forecasts of 100 degrees or more or of -10 degrees or less appear with no spaces between them.

5. DPT - SURFACE DEW POINT

KALI	B 2	AVN	MOS	G	JIDZ	NCE	C	10/	24/	200	00	000	0Ο τ	JTC								
DT ,	/OCT	24					/00	ст 2	25						/00	ст 2	26				/	
HR	06	09	12	15	18	21	00	03	06	09	12	15	18	21	00	03	06	09	12	18	00	
DPT	25	23	23	24	23	23	24	26	28	28	30	32	34	37	39	41	43	43	45	45	44	

Time-specific 2-m dew point forecasts are valid every 3 hours from 6 to 60 hours, and then every 6 hours to 72 hours after 0000 and 1200 UTC. These forecasts are valid at 0600, 0900,..., 2100, 0000 UTC, and so forth. Each dew point forecast is presented to the nearest whole degree Fahrenheit; a missing forecast is indicated by a 999. Three characters are available for the dew

point forecasts so that two consecutive forecasts of -10 degrees or less appear with no spaces between them.

6. CLD - TOTAL SKY COVER CATEGORIES

 KALB
 AVN
 MOS
 GUIDANCE
 10/24/2000
 0000
 UTC

 DT
 /OCT
 24
 /OCT
 25
 /OCT
 26
 /

 HR
 06
 09
 12
 15
 18
 21
 00
 03
 06
 09
 12
 18
 00
 ...

 CLD
 CL
 <t

Forecast categories of total sky cover (see the following table) are available in plain language for projections at 3-h intervals from 6 to 60 hours, and then every 6 hours to 72 hours after the initial data times (0000 and 1200 UTC). All forecasts are valid for specific times (i.e., 0600, 0900, 1200, and so forth). Two characters identify the category (CL - clear; SC scattered; BK - broken; OV - overcast); a missing forecast is denoted by XX.

> Total Sky Cover Categories CL - clear; SC - > 0 to 4 octas of total sky cover; BK - > 4 to < 8 octas of total sky cover; OV - 8 octas of total sky cover or totally obscured.

7. WDR - SURFACE WIND DIRECTION / WSP - SURFACE WIND SPEED

KALE	3 <i>1</i>	AVN	MOS	G GT	JIDZ	ANCE	2	10/	24/	/200	00	000	τ ΟΟ	JTC							
DT /	'OCT	24					/00	ст 2	25						/00	СТ 2	26				1
HR	06	09	12	15	18	21	00	03	06	09	12	15	18	21	00	03	06	09	12	18	00
WDR	32	32	32	31	31	32	32	00	00	00	36	15	16	15	16	16	16	16	18	18	19
WSP	08	08	08	11	12	09	02	00	00	00	01	04	10	08	04	06	08	06	11	12	8

Surface wind direction (WDR) and speed (WSP) forecasts are given at 3-h intervals for projections of 6 to 60 hours, and then every 6 hours to 72 hours after the initial data times (0000 and 1200 UTC). These are forecasts of the 10-m winds (a 2-minute average) at specific times throughout each day (i.e., 0600, 0900, 1200 UTC, and so forth). The wind direction is given in tens of degrees and varies from 01 (10 degrees) to 36 (360 degrees). The normal meteorological convention for specifying wind direction is followed. The wind speed is given in knots; the maximum speed allowed in the message is 98 knots. For both direction and speed, missing forecasts are denoted by 99. A calm wind is indicated by a wind direction and speed of 00.

8. P06 - PROBABILITY OF PRECIPITATION IN A 6-H PERIOD

KALB AVN	MOS GUI	IDANCE 10)/24/2000	0000 UTC	3		
DT /OCT 24		/oct	25		/OCT 26	5	/
HR 06 09	12 15 1	18 21 00 03	3 06 09 1	2 15 18 21	L 00 03 0	06 09 1	2 18 00
				•			
P06	0	0 0	3	50	0	9 1	4 15 20
The P06 for							
equivalent p	precipita	ation (PoP)	occurring	g during a	6-h perio	d. The	6-h PoP's
are valid f	or interv	vals of 6-12	2, 12-18,	18-24, 24-3	30, 30-36	, 36-42	, 42-48, 48-
54, 54-60,	60-66, an	nd 66-72 hou	urs after	the initia	l data ti	mes (00	00 and
1200 UTC).	In the r	message, the	e forecast	values are	e display	ed unde	r the ending

time of the 6-h period. The probability is given to the nearest percent. Values range from 0 to 100%. A missing forecast value is indicated by 999.

9. P12 - PROBABILITY OF PRECIPITATION IN A 12-H PERIOD

KAL	в	AVN	MOS	GU GU	JIDF	NCE	2	10/	24/	200	00	000	0 U	JTC								
DT	/OCT	24					/00	ст 2	25						/00	т 2	26				/	
HR	06	09	12	15	18	21	00	03	06	09	12	15	18	21	00	03	06	09	12	18	00	
P12	1						0				6				0				17		25	
р12							0				~				0				17		25	

The P12 forecasts are for the probability of 0.01 inches or more of liquidequivalent precipitation (PoP) occurring during a 12-h period. For nearly all stations, the 12-h PoP's are valid for intervals of 12-24, 24-36, 36-48, 48-60, and 60-72 hours after the initial data times (0000 and 1200 UTC). For stations in Hawaii, however, the 12-h PoP's are valid for intervals of 6-18, 18-30, 30-42, 42-54, and 54-66 hours after 0000 and 1200 UTC. In the message, the forecast values are displayed under the ending time of the 12-h period. The probability is given to the nearest percent. Values range from 0 to 100%. A missing forecast value is indicated by 999.

10. Q06 - QUANTITATIVE PRECIPITATION AMOUNT IN A 6-H PERIOD

KALI	B <i>1</i>	AVN	MOS	GU	JIDA	ANCE	2	10/	/24/	200	00	000)O T	JTC							
DT ,	/OCT	24					/00	ст 2	25						/00	ст 2	26				1
HR	06	09	12	15	18	21	00	03	06	09	12	15	18	21	00	03	06	09	12	18	00
Q06			0		0		0		0		0		0		0		0		0	0	0

Guidance for liquid-equivalent precipitation amount (QPF) accumulated during a 6-h period is presented in categorical form. These forecasts are available for projections of 6-12, 12-18, 18-24, 24-30, 30-36, 36-42, 42-48, 48-54, 54-60, 60-66, and 66-72 hours after the initial data time (0000 and 1200 UTC). The forecasts are displayed beneath the hour indicating the end of the 6-h period. The QPF guidance is a categorical forecast of liquid-equivalent precipitation equaling or exceeding certain specified amounts in the 6-h periods. The categories are as follows:

<u>QPF Categories</u> 0 = no precipitation expected; 1 = 0.01 - 0.09 inches; 2 = 0.10 - 0.24 inches; 3 = 0.25 - 0.49 inches; 4 = 0.50 - 0.99 inches; 5 = \geq 1.00 inches.

Missing forecasts are denoted by 9.

11. Q12 - QUANTITATIVE PRECIPITATION AMOUNT IN A 12-H PERIOD

K/	ALB	A۱	VN	MOS	GU	JIDF	NCE	<u>.</u>	10/	/24/	200	00	000	0 τ	JTC								
D'	г /ос	т 2	24					/00	ст 2	25						/00	т 2	26				/	
H	R ()6 (09	12	15	18	21	00	03	06	09	12	15	18	21	00	03	06	09	12	18	00	

Q12	0	0	0	0	1

Guidance for liquid-equivalent precipitation amount (QPF) accumulated during a 12-h period is presented in categorical form. These forecasts are available for projections of 12-24, 24-36, 36-48, 48-60, and 60-72 hours after the initial data time (0000 and 1200 UTC). For stations in Hawaii, however, the 12-h QPF's are valid for intervals of 6-18, 18-30, 30-42, 42-54, and 54-66 hours after 0000 and 1200 UTC. The forecasts are displayed beneath the hour indicating the end of the 12-h period. The QPF guidance is a categorical forecast of liquid-equivalent precipitation equaling or exceeding certain specified amounts in the 12-h periods. The categories are as follows:

<u>QPF Categories</u> 0 = no precipitation expected; 1 = 0.01 - 0.09 inches; 2 = 0.10 - 0.24 inches; 3 = 0.25 - 0.49 inches; 4 = 0.50 - 0.99 inches; 5 = 1.00 - 1.99 inches; 6 = \geq 2.00 inches.

Missing forecasts are denoted by 9.

12. T06 - PROBABILITY OF THUNDERSTORMS/CONDITIONAL PROBABILITY OF SEVERE THUNDERSTORMS IN A 6-H PERIOD

KAL	B.	AVN	MOS	S GI	UID	ANCI	2	10/	24	/20	00	000	00 1	JTC							
DT	/OCT	24					/00	СТ 2	25						/00	ст 2	26				1
HR	06	09	12	15	18	21	00	03	06	09	12	15	18	21	00	03	06	09	12	18	00
т06		0	/ 7	0	/ 1	0,	/ 2	0/	4	2	/ 1	1,	/ 1	2,	/ 1	18,	/ 3	4	/ 2	22	/ 3

The T06 line represents forecasts for the probability of thunderstorms (to the left of the diagonal) and the conditional probability of severe thunderstorms (to the right of the diagonal) during a 6-h period. The 6-h probability forecasts are valid for intervals of 6-12, 12-18, 18-24, 24-30, 30-36, 36-42, 42-48, 48-54, 54-60, and 66-72 hours after the initial data times (0000 and 1200 UTC). Because of the line width, the 60-66 h forecast is not available. In the message, the pair of forecast values is displayed under the ending time of the 6-h period. The thunderstorm probability is given to the nearest whole percent. Values range from 0 to 100%. A missing forecast value is indicated by 999. The conditional severe thunderstorm probability is given to the nearest whole percent. Values range from 0 to 98%. A missing forecast value is given by 99. Both the thunderstorm and conditional severe storm probabilities are available year-round for stations in the contiguous U.S. Note that these probabilities represent the likelihood of the event within a box approximately 47 km on a side and containing the station specified. Forecasts are unavailable for stations in Alaska, Hawaii, or Puerto Rico because reports from the National Lightning Detection Network used to define the thunderstorm predictand were unavailable for locations in those areas.

13. T12 - PROBABILITY OF THUNDERSTORMS/CONDITIONAL PROBABILITY OF SEVERE THUNDERSTORMS IN A 12-H PERIOD

KAI	ЪB	AVN	MOS	G	UIDZ	ANCI	Ξ	10,	/24/	/200	00	000	00 1	JTC								
DT	/OCT	24					/00	ст 2	25						/00	СТ 2	26				1	
HR	06	09	12	15	18	21	00	03	06	09	12	15	18	21	00	03	06	09	12	18	00	

. . .

т12	0/7	0/3	4/2	14/ 4	10/ 3	
-----	-----	-----	-----	-------	-------	--

The T12 line represents forecasts for the probability of thunderstorms (to the left of the diagonal) and the conditional probability of severe thunderstorms (to the right of the diagonal) occurring during a 12-h period. The 12-h probability forecasts are valid for intervals of 6-18, 18-30, 30-42, 42-54, and 54-66 hours after the initial data times (0000 and 1200 UTC). In the message, the pair of forecast values is displayed under the ending time of the 12-h period. The thunderstorm probability is given to the nearest whole percent. Values range from 0 to 100%. A missing forecast value is indicated by 999. The conditional severe thunderstorm probability is given to the nearest whole percent. Values range from 0 to 98%. A missing forecast value is given by 99. Both the thunderstorm and conditional severe storm probabilities are available year-round for stations in the contiguous U.S. These probabilities represent the likelihood of the event within a box approximately 47 km on a side and containing the station specified. Forecasts are unavailable for stations in Alaska, Hawaii, or Puerto Rico because reports from the National Lightning Detection Network used to define the thunderstorm predictand were unavailable for locations in those areas.

14. POZ - PROBABILITY OF FREEZING PRECIPITATION (CONDITIONAL)

KA	LB	AVN	MOS	GU	JIDA	NCE	2	10/	/24/	200	00	000)Ο τ	JTC								
DT	/00	т 24					/00	ст 2	25						/00	ст 2	26				/	
HF	٤ ٥	6 09	12	15	18	21	00	03	06	09	12	15	18	21	00	03	06	09	12	18	00	
PC	Z	0 0	5	9	11	9	15	13	7	10	5	0	0	0	0	1	0	1	0	0	0	

Conditional probability of freezing precipitation (given that precipitation is occurring) forecasts are available for specific times every 3 hours from 6 to 60 hours and then every 6 hours to 72 hours after 0000 and 1200 UTC. Freezing precipitation is defined as the occurrence of freezing rain or drizzle, ice pellets (sleet), or any mixture of freezing rain, drizzle, or ice pellets with other precipitation types. The probabilities are given to the nearest whole percent, and values range from 0 to 100%. Missing values are indicated by 999. These probabilities are used in producing the categorical TYP forecast described in Section 16. The POZ guidance is transmitted during the period of September 1 - May 31. Because of the rarity of the freezing rain event, many stations do not have forecast equations for the POZ category. In these cases, the POZ line is not in the message at any time of the year.

15. POS - PROBABILITY OF SNOW (CONDITIONAL)

KALB	3 2	AVN	MOS	G G	JID	ANC	E	10,	/24,	/200	00	000	00 τ	JTC							
DT /	OCT	24					/00	ст 2	25						/00	ст 2	26				1
HR	06	09	12	15	18	21	00	03	06	09	12	15	18	21	00	03	06	09	12	18	00
POS	84	90	95	90	75	47	35	16	20	5	6	0	0	0	0	1	1	1	0	0	0
Cond	itio	nal	pro	bab	ili	ty d	of s	now	(gi	iven	th	at p	prec	ipi	tat	Lon	is	occ	urri	lng)	
fore	cast	s ai	ce a	vai	lab	le f	Eor	spe	cifi	ic t	ime	s ev	very	3	houi	rs f	from	6	to 6	50 h	ours
and	then	eve	ery	6 h	our	s to	o 72	ho	urs	aft	er	0000) an	d 1	200	UTC	2.	Sno	w is	s de	fined
as tl	he o	ccui	ren	ce	of a	a pı	ıre	sno	w ev	vent	, t	hat	is,	sn	ow,	sno	w s	how	ers,	sn	WO
grai	ns,	or s	snow	pe	lle	ts d	or a	ny	comk	oina	tio	n of	ī th	ose	ele	emer	nts.	S	now	mix	ed with
rain	is	cons	side	red	a	liqu	uid	pre	cipi	itat	ion	eve	ent.	Т	he p	prok	babi	lit	ies	are	given
to tl	he n	eare	est	who	le j	perd	cent	, a	nd v	zalu	es	ranc	ge f	rom	0 t	to 1	.00%	. 1	Miss	sing	values
are :	indi	cate	ed b	y 9	99.	Tł	nese	pr	obak	oili	tie	s ar	ce u	sed	in	pro	oduc	ing	the	e ca	tegori-
cal :	TYP	fore	ecas	t d	esc	ribe	ed i	n S	ecti	ion	16.	Tł	ne P	POS	guid	danc	ce i	s t	rans	smit	ted
only	dur	ing	the	pe	rio	d of	E Se	pte	nbeı	r 1	- M	ay 3	31.	Al	thou	ıgh	the	CO	ndit	cion	al

probability of liquid precipitation is not given in the message, the probability can be inferred since the sum of the probability of freezing precipitation, snow, and liquid precipitation is 100%.

16. TYP - PRECIPITATION TYPE FORECASTS (CONDITIONAL)

KAL	B.	AVN	MOS	S GT	JID	ANCI	C	10,	/24,	/200	00	000)O (JTC								
DT	/OCT	24					/00	ст 2	25						/00	ст 2	26				1	
HR	06	09	12	15	18	21	00	03	06	09	12	15	18	21	00	03	06	09	12	18	00	
TYP	S	S	S	S	S	S	S	R	R	R	R	R	R	R	R	R	R	R	R	R	R	

The TYP line represents forecasts of precipitation type (if precipitation occurs) for specific times every 3 hours from 6 to 60 hours, and then every 6 hours to 72 hours after the initial hour of 0000 or 1200 UTC. The forecast is indicated by one character where "Z" represents freezing precipitation (freezing rain, freezing drizzle, ice pellets (sleet), or any report of these elements mixed with other precipitation types), "S" represents snow (snow, snow grains, snow pellets, or snow showers), and "R" represents liquid precipitation (rain, drizzle, or a mixture of rain or drizzle with snow). A missing forecast is denoted by "X". The precipitation type guidance is transmitted only during the period of September 1 - May 31.

17. SNW - SNOWFALL AMOUNT CATEGORICAL FORECAST

F	KAL	в	AVN	MOS	GU	JIDZ	ANCI	2	10,	/24,	/200	00	000	00 1	JTC								
Γ	ЭТ	/oct	24					/00	ст 2	25						/00	ст 2	26				1	
F	IR	06	09	12	15	18	21	00	03	06	09	12	15	18	21	00	03	06	09	12	18	00	
S	SNW	,										0								0			

Categorical forecasts of snowfall amount are available in the message for 24-h periods ending approximately 36 and 60 hours after 0000 UTC and approximately 24, 48, and 72 hours after 1200 UTC. Since observations from the cooperative observer network are used to define the event, the valid times are approximations. The categories are denoted as follows:

Snowfall Amount Categories 0 = no snow or a trace expected; 1 = > a trace to < 2 inches expected; 2 = 2 to < 4 inches; $4 = \ge 4 \text{ to } < 6 \text{ inches;}$ $6 = \ge 6 \text{ to } < 8 \text{ inches;}$ $8 = \ge 8 \text{ inches.}$

A missing forecast is denoted by 9; forecasts are disseminated only for the period of September 1 - May 31.

18. CIG - CEILING HEIGHT CATEGORICAL FORECASTS

KALE	3 2	AVN	MOS	S GI	JID	ANCI	2	10,	/24,	/200	00	000	00 1	JTC								
DT /	OCT	24					/00	ст 2	25						/00	ст 2	26				1	
HR	06	09	12	15	18	21	00	03	06	09	12	15	18	21	00	03	06	09	12	18	00	
CIG	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	

Forecasts of seven categories of ceiling height (see the following table) are available for specific times valid every 3 hours from 6 to 60 hours and then every 6 hours to 72 hours after 0000 and 1200 UTC. The forecasts are displayed beneath the time of the day for which they are valid. Values of 1 through 7 are allowed for the categorical guidance; a value of 9 denotes a missing forecast. The categories are as follows:

Ceiling Height Categories
1 = ceiling height of < 200 feet;
2 = ceiling height of 200 - 400 feet;
3 = ceiling height of 500 - 900 feet;
4 = ceiling height of 1000 - 3000 feet;
5 = ceiling height of 3100 - 6500 feet;
6 = ceiling height of 6600 - 12,000 feet;
7 = ceiling height of > 12,000 feet or unlimited ceiling.

The categorical guidance is prepared by using probability forecasts of the same categories.

19. VIS - VISIBILITY CATEGORICAL FORECASTS

KAI	св и	AVN	MOS	G GT	JIDA	ANCE	2	10/	/24/	200	00	000	τ 00	JTC								
DT	/OCT	24					/00	ст 2	25						/00	СТ 2	26				1	
HR	06	09	12	15	18	21	00	03	06	09	12	15	18	21	00	03	06	09	12	18	00	
VIS	5 7	7	7	7	7	7	7	7	7	7	5	7	7	7	7	5	5	2	5	6	7	

Forecasts of seven categories of visibility (see the following table) are available for specific times valid every 3 hours from 6 to 60 hours and then every 6 hours to 72 hours after 0000 and 1200 UTC. The forecasts are displayed beneath the time of the day for which they are valid. Values of 1 through 7 are allowed for the categorical guidance; a value of 9 denotes a missing forecast. The categories are as follows:

> <u>Visibility Categories</u> 1 = visibility $\leq 1/4$ mi; 2 = visibility of > 1/4 mi to $\leq 1/2$ mi; 3 = visibility of > 1/2 mi to < 1 mi; 4 = visibility of 1 to < 3 mi; 5 = visibility of 3 to 5 mi; 6 = visibility of 6 mi; 7 = visibility of > 6 mi.

The categorical guidance is prepared by using probability forecasts of the same categories.

20. OBV - OBSTRUCTION TO VISION CATEGORICAL FORECASTS

KALB AVN MOS GUIDANCE 10/24/2000 0000 UT	
DT /OCT 24 /OCT 25	/ост 26 /
HR 06 09 12 15 18 21 00 03 06 09 12 15 18 2	00 03 06 09 12 18 00
OBV NNNNNNNN NHZNN	N HZ HZ FG HZ HZ N

Forecasts of five categories of obstruction to vision (see the following table) are available for specific times valid every 3 hours from 6 to 60 hours and then every 6 hours to 72 hours after 0000 and 1200 UTC. The forecasts are displayed in plain language beneath the time of the day for which they are valid. The categories are denoted by the letters "N", "HZ", "BR", "FG", and

"BL"; a value of "X" denotes a missing forecast. The categories are as follows:

```
<u>Obstruction to Vision Categories</u>

N = none of the following;

HZ = haze, smoke, dust;

BR = mist (fog with visibility ≥ 5/8 mi);

FG = fog or ground fog (visibility < 5/8 mi);

BL = blowing dust, sand, snow.
```

The categorical guidance is prepared by using probability forecasts of the same categories. In the equation development, cases of fog or mist were not stratified by the occurrence of precipitation. Thus, a forecast of fog can be coincidental with a forecast of precipitation. Lower visibilities caused exclusively by precipitation occurrence are not indicated by the obstruction to vision guidance.

21. AVAILABILITY

The 0000 and 1200 UTC AVN MOS guidance is available at approximately 0430 and 1630 UTC, respectively, in 10 alphanumeric messages transmitted to NWS AWIPS and Family of Services (FOS) circuits: six containing guidance for stations in the contiguous U.S., Puerto Rico, and the Virgin Islands; three containing guidance for Alaskan sites; and one containing guidance for stations in Hawaii. The following two-line WMO headers are used:

WMO Header - Region FOPA20 KWNO - Pacific Region MAVPAO FOUS21 KWNO - Northeast U.S. MAVNE1 FOUS22 KWNO - Southeast U.S. MAVSE1 FOUS23 KWNO - North Central U.S. MAVNC1 FOUS24 KWNO - South Central U.S. MAVSC1 FOUS25 KWNO - Rocky Mountain Region MAVRM1 FOUS26 KWNO - West Coast Region MAVWC1 FOAK37 KWNO - Southeast Alaska (Juneau) MAVAJK FOAK38 KWNO - Central Alaska (Anchorage) MAVAFC FOAK39 KWNO - Northern Alaska (Fairbanks) MAVAFG

The messages for a subset of the stations in the above collectives are also sent to AFWA for dissemination on military communication circuits. Twentyseven messages contain guidance for stations in the contiguous U.S., three messages contain guidance for Alaskan sites, one message contains guidance for Hawaiian sites, and one message contains guidance for stations in Puerto Rico. The following WMO headers are used:

> WMO Header - Region FOUS30 KWNO - Contiguous U.S. MAVFxx, where xx=01 through 27 FOAK30 KWNO - Alaska MAVFxx, where xx=50, 51, or 52 FOPA30 KWNO - Hawaii MAVF70 FOCA30 KWNO - Puerto Rico MAVF80

22. STATION LIST

As of August 2001, the AVN MOS guidance was available for 1060 stations in the ten bulletins transmitted to AWIPS and on the NWS FOS. Guidance for another 346 sites will be added in late 2001. As of September 2001, the AVN MOS guidance is available for 273 stations in the messages transmitted to AFWA. The user may check the following home pages for the station lists and corresponding WMO headers:

http://www.nws.noaa.gov/mdl/synop/stadrg.htm

http://www.nws.noaa.gov/mdl/synop/afstadrg.htm

The first address provides station lists for the AWIPS/FOS messages; the second address provides station lists for the military bulletins.

Figure 1. Sample 0000 UTC message.

KALB	ž	AVN	MOS	S GI	JIDA	ANCE	2	10/	/24/	/200	0	000) O (JTC							
DT /	OCT	24						CT 2							/00	CT 2	26				/
HR	06	09	12	15	18	21	00	03	06	09	12	15	18	21	00	03	06	09	12	18	00
X/N							49				30				61				43		61
TMP	32	30	30	41	47	47	38	34	32	32	34	47	58	60	54	50	48	47	49	57	53
DPT	25	23	23	24	23	23	24	26	28	28	30	32	34	37	39	41	43	43	45	45	44
CLD	CL	CL	CL	CL	CL	CL	CL	CL	SC	SC	CL	CL	CL	CL	CL	CL	CL	SC	SC	SC	SC
WDR	32	32	32	31	31	32	32	00	00	00	36	15	16	15	16	16	16	16	18	18	19
WSP	08	08	08	11	12	09	02	00	00	00	01	04	10	08	04	06	8 0	06	11	12	8
P06			0		0		0		3		5		0		0		9		14	15	20
P12							0				6				0				17		25
Q06			0		0		0		0		0		0		0		0		0	0	0
Q12							0				0				0				0		1
Т06		0,	/ 7	0,		0,	/ 2	0 /		2/	′1	1/	-	27	/ 1	18,	/ 3	4,	_	22/	/ 3
т12				0,	/ 7			0 /	/ 3			4/	2			14/	/ 4		10,	/ 3	
POZ	0	0	5	9	11	9	15	13	7	10	5	0	0	0	0	1	0	1	0	0	0
POS	84	90	95	90	75	47	35	16	20	5	6	0	0	0	0	1	1	1	0	0	0
TYP	S	S	S	S	S	S	S	R	R	R	R	R	R	R	R	R	R	R	R	R	R
SNW											0								0		
CIG	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7
VIS	7	7	7	7	7	7	7	7	7	7	5	7	7	7	7	5	5	1	5	6	7
OBV	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	ΗZ	Ν	Ν	Ν	Ν	ΗZ	ΗZ	FG	ΗZ	ΗZ	Ν

Figure 2. Sample 1200 UTC message.

KALB	Ž	AVN	MOS	s Gt	JIDZ	ANCE	£	11/	24/	/200	0	120) O (JTC							
DT /	NOV	24	/NO	DV 2	25						/NC	DV 2	26						/NC	DV 2	27
HR	18	21	00	03	06	09	12	15	18	21	00	03	06	09	12	15	18	21	00	06	12
N/X							38				47				37				51		38
TMP	61	59	55	50	46	42	39	43	45	44	39	39	39	41	40	43	48	48	47	43	39
DPT	55	53	49	44	38	34	31	31	31	31	33	33	35	37	38	41	43	44	43	41	38
CLD	SC	ΒK	ΒK	OV	SC	SC	SC	ΒK	OV	OV	OV	OV	OV	OV	OV	OV	OV	OV	OV	OV	OV
WDR	17	17	20	24	26	30	31	34	01	01	00	00	05	09	13	13	13	12	14	16	15
WSP	12	10	08	08	05	05	05	02	02	02	00	00	03	03	07	03	03	02	05	04	03
P06			26		30		16		8		23		29		44		55		54	45	51
P12							36				23				51				70		65
Q06			1		0		0		0		0		0		1		1		2	1	1
Q12							1				0				1				3		2
Т06		9,	/ 2	2,	-	2,	/ 4	1/		0/	0	27	-	7,	/ 0	8,		5/		8,	/ 3
Т12				9,				27	4			1/	-			12,	/ 1		10/		
PZP	0	0	4	2	5	2	10	15	8	3	3	2	3	4	4	6	0	1	5	0	1
PSN	0	0	0	0	1	4	4	6	6	5	1	3	3	6	8	5	7	8	8	6	3
TYP	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
SNW							0								0						0
CIG	7	4	4	4	7	7	7	7	7	6	5	5	4	5	4	4	4	4	4	4	4
VIS	7	7	7	7	7	7	7	7	7	7	7	2	2	1	2	5	7	7	7	2	2
OBV	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	Ν	FG	FG	FG	FG	ΗZ	Ν	Ν	Ν	FG	FG